

**Qualität : seemee[®] projection screen
white / white**

B 3122

Faserstoff des Trägergewebes: support cloth tissu natura del supporto	(DIN 60001)	PES
Fadendichte K/S pro cm ends/picks nombre de fil numero dei fili	(DIN EN ISO 1049-2)	9/10
Garnfeinheit dtex K/S yarn finesse du fil tiolo del filo	(DIN EN ISO 2060)	2200/0,3 mono
Bindung weave armure tipo di tessitura	(DIN ISO 9354)	1/1 plain
Flächengewicht g/m2 (Rohw) greycloth-weight poids du tissu support peso del supporto	(DIN EN ISO 2286-2)	300
Beschichtungsart type of coating nature de l'enduit natura della spalmatura		PVC coated on both sides
Flächengewicht g/m2 (Ges) total weight masse totale peso totale	(DIN EN ISO 2286-2)	800
Breite (cm) width largeur larghezza	(DIN EN ISO 2286-1)	400/515
Reißkraft (N/5cm) K/S tensile strength warp/weft resistance a la traction en chaine/en trame resistenza alla trazione ordito/trama	(DIN 53354)	5000/1600
Weiterreißfestigk. Trapez (N) K/S tear resistance warp/weft	(DIN 53363)	200/700
Bemerkungen: remarks remarques rimarchi	application:	projection screen

**flame retardant according to:
DIN 4102 B1**