

**Qualität : seemie<sup>®</sup> projection screen  
white / black**

**B 3222**

<b>Faserstoff des Trägergewebes:</b> support cloth tissu natura del supporto	<b>(DIN 60001)</b>	<b>PES</b>
<b>Fadendichte K/S pro cm</b> ends/picks nombre de fil numero dei fili	<b>(DIN EN ISO 1049-2)</b>	<b>9/10</b>
<b>Garnfeinheit dtex K/S</b> yarn finesse du fil tiolo del filo	<b>(DIN EN ISO 2060)</b>	<b>2200/0,3 mono</b>
<b>Bindung</b> weave armure tipo di tessitura	<b>(DIN ISO 9354)</b>	<b>1/1 plain</b>
<b>Flächengewicht g/m2 (Rohw)</b> greycloth-weight poids du tissu support peso del supporto	<b>(DIN EN ISO 2286-2)</b>	<b>300</b>
<b>Beschichtungsart</b> type of coating nature de l'enduit natura della spalmatura		<b>PVC coated on both sides (reverse side black)</b>
<b>Flächengewicht g/m2 (Ges)</b> total weight masse totale peso totale	<b>(DIN EN ISO 2286-2)</b>	<b>800</b>
<b>Breite ( cm)</b> width largeur larghezza	<b>(DIN EN ISO 2286-1)</b>	<b>400/515</b>
<b>Reißkraft (N/5cm) K/S</b> tensile strength warp/weft resistance a la traction en chaine/en trame resistenza alla trazione ordito/trama	<b>(DIN 53354)</b>	<b>5000/1600</b>
<b>Weiterreißfestigk. Trapez (N) K/S</b> tear resistance warp/weft	<b>(DIN 53363)</b>	<b>200/700</b>
<b>Bemerkungen:</b> remarks remarques rimarchi	<b>application:</b>	<b>projection screen</b>

**flame retardant according to:  
DIN 4102 B1**