

**Qualität: seemee<sup>®</sup> insight light****B4050**

<b>Faserstoff des Trägergewebes:</b> support cloth tissu natura del supportc	<b>(DIN 60001)</b>	<b>PES</b>
<b>Fadendichte K/S pro cm</b> ends/picks nombre de fi numero dei fil	<b>(DIN EN 1049-2)</b>	<b>18/25</b>
<b>Garnfeinheit dtex K/S</b> yarn finesse du fil tiolo del filc	<b>(DIN EN ISO 2060)</b>	<b>280</b>
<b>Bindung</b> weave armure tipo di tessitura	<b>(DIN ISO 9354)</b>	<b>1/1 plain</b>
<b>Flächengewicht g/m2 (Rohw)</b> greycloth-weight poids du tissu support peso del supportc	<b>(DIN EN ISO 2286-2)</b>	<b>130</b>
<b>Beschichtungsart</b> type of coating nature de l'endui natura della spalmatura		<b>acrylat coated on both sides</b>
<b>Flächengewicht g/m2 (Ges)</b> total weight masse totale peso totale	<b>(DI EN ISO 2286-2)</b>	<b>230</b>
<b>Breite ( cm)</b> width largeur larghezza	<b>(DIN EN ISO 2286-1)</b>	<b>200/300/500</b>
<b>Reißkraft (N/5cm) K/S</b> tensile strength warp/wef resistance a la traction en chaine/en tram resistenza alla trazione ordito/tram	<b>(DIN 53354)</b>	<b>1500/1500</b>
<b>Bemerkungen:</b> remarks remarques rimarchi	<b>application:</b>	<b>for indoor use computer spray printable on Vutek,NUR,Scitex,etc. printable finish on both sides</b>

**flame retardant according to  
DIN4102B1**